



Project: _____

Item #: _____ Quantity: _____

Model #: _____



●SRC-2-181SS (110-240 Volt / US)



Induction Cooking Station

Unit contains two (2) SM-181R, MAX Induction™ flush-mounted induction ranges, inside a wood cabinet with a SmartStone™ top.

This portable unit is customized by you ~ you choose the wood tone and the SmartStone™ countertop color.

Cabinets can be used for demonstration cooking, or can be used as 'hold-only' ranges for keeping food at proper holding temperature.

Perfect application for tabletop buffets, suite service, private parties or display cooking. Controls face the Operator or Chef.

[EC] Electric Requirements:

Model	Voltage	Phase	Hertz	Watts	Amps	Plug
Two (2) SM-181R	110-120 Volt/US	1	50-60	1800 Watts Each Range	15 Amps Each Range	Two (2) NEMA 5-15P 3-Prong (6' Cord)

Notes & Conditions:

1. Ensure that you have dedicated power wherever you are planning to use your induction range. Refer to the Installation & Operation Manual for detailed instructions regarding power requirements & operating instructions.
2. MAX Induction™ Ranges require use of ferrous metal, induction-ready cookware.
3. Approximate dimensions are 33.50" W x 20.125" D x 6" H. Shipping weight is approximately 41 pounds.
4. Approvals: FCC, ETL, ETL to NSF4

Due to continuous product improvement, specifications are subject to change without notice